

SHRINK TUNNEL

MODEL: T3417



FEATURES

TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Dual Mechanical Controls
- Open Coil Heating Element Guaranteed for 10 Years
- Two Heat Zones
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life

CONVEYOR FEATURES

- Quick Change 1/2" Diameter Live/Dead Rollers with 2" Spacing
- Unique Pre-Shrink Feature Allows For 25% More Bottom Shrink
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 70 Feet Per Minute



Model T3417

OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	34" L, 17" W, 8" H (86 cm L, 43 cm W, 20 cm H)
CONVEYOR	Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 2"
CONVEYOR SPEED	0 - 30 ft./min. (9 m./min.) 0 - 70 ft./min. LDR (0 - 21 m./min. LDR)
OVERALL DIMENSIONS	59" L, 26.25" W, 58" H (150 cm L, 67 cm W, 147 cm H)
POWER REQUIREMENTS	220 Volts, 8" H 43 Amps; 10"H 54 Amps Single Phase
WATTAGE	8,000 Watts
WEIGHT	560 lbs. (255 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (T3417S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Non-stick Mesh Belt Overlay (for Live/Dead Roller Conveyor)
- Roller Spacing: 1"
- Roller Spacing: 1 1/2"
- Pack Cooler Fan (For Polyethylene)
- Hydraulic Easy Lift Adjustable Height Console
- 10" High Tunnel Opening
- Left Hand Reverse Flow

